

SPECIFICATIONS:

PSI/Temp Rating: 250 PSI/400°F
Cartridge: AISI Type 304 Stainless Steel
 AISI Type 17-7 PH Stainless Steel
Body Material: 1/2", 1/2"L, 3/4": Brass; Other sizes:
 Wrought Copper ASTM B75-66 Type 122
Assembly: Valve comes fully assembled.

FLOW RATES (+/- 5%)

SIZE ¹	MODEL NO	PSID RANGE	GPM
1/2"	3C021	2-32	0.25, 0.33, 0.50, 1.00, 1.50, 2.00, 2.50, 3.00
	3C041	4-57	0.50, 1.00, 1.50, 2.00, 2.50, 3.00
1/2"L	3271L	1-14	.33, .50, .67, 1.00, 1.33, 1.67, 2.00, 2.33, 2.67, 3.33, 4.00, 4.67, 5.00
	3272L	2-32	.55, .75, 1.00, 1.50, 2.00, 2.50, 3.00, 3.50, 4.00, 5.00, 6.00, 7.00, 8.00
	3274L	4-57	.75, 1.00, 1.33, 2.00, 2.67, 3.33, 4.00, 4.67, 5.33, 6.67, 8.00, 9.33, 10.00
	3278L	8-128	1.10, 1.50, 2.00, 3.00, 4.00, 5.00, 6.00, 7.00, 8.00, 10.00, 12.00, 14.00, 16.00
3/4"	3551L	1-14	.33, .50, .67, 1.00, 1.33, 1.67, 2.00, 2.33, 2.67, 3.33, 4.00, 4.67, 5.00
	3552L	2-32	.55, .75, 1.00, 1.50, 2.00, 2.50, 3.00, 3.50, 4.00, 5.00, 6.00, 7.00, 8.00
	3554L	4-57	.75, 1.00, 1.33, 2.00, 2.67, 3.33, 4.00, 4.67, 5.33, 6.67, 8.00, 9.33, 10.00
	3558L	8-128	1.10, 1.50, 2.00, 3.00, 4.00, 5.00, 6.00, 7.00, 8.00, 10.00, 12.00, 14.00, 16.00
1"	3561L _	1-14	3.0, 3.33, 4.00, 4.67, 5.33, 6.00, 6.67, 7.33, 8.00, 8.67, 9.33, 10.00, 10.67, 11.33, 12.00, 12.67, 13.33, 14.00, 14.67
	3562L _	2-32	4.5, 5.0, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0, 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	3564L _	4-57	6.00, 6.67, 8.00, 9.33, 10.67, 12.00, 13.33, 14.67, 16.00, 17.33, 18.67, 20.00, 21.33, 22.67, 24.00, 25.33, 26.67, 28.00, 29.33
	3568L _	8-128	9.0, 10.0, 12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 24.0, 26.0, 28.0, 30.0, 32.0, 34.0, 36.0, 38.0, 40.0, 42.0, 44.0
1-1/4"	3671L _	1-14	3.0, 3.33, 4.00, 4.67, 5.33, 6.00, 6.67, 7.33, 8.00, 8.67, 9.33, 10.00, 10.67, 11.33, 12.00, 12.67, 13.33, 14.00, 14.67
	3672L _	2-32	4.5, 5.0, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0, 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	3674L _	4-57	6.00, 6.67, 8.00, 9.33, 10.67, 12.00, 13.33, 14.67, 16.00, 17.33, 18.67, 20.00, 21.33, 22.67, 24.00, 25.33, 26.67, 28.00, 29.33
	3678L _	8-128	9.0, 10.0, 12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 24.0, 26.0, 28.0, 30.0, 32.0, 34.0, 36.0, 38.0, 40.0, 42.0, 44.0
1-1/2"	3711L _	1-14	3.0, 3.33, 4.00, 4.67, 5.33, 6.00, 6.67, 7.33, 8.00, 8.67, 9.33, 10.00, 10.67, 11.33, 12.00, 12.67, 13.33, 14.00, 14.67
	3712L _	2-32	4.5, 5.0, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0, 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	3714L _	4-57	6.00, 6.67, 8.00, 9.33, 10.67, 12.00, 13.33, 14.67, 16.00, 17.33, 18.67, 20.00, 21.33, 22.67, 24.00, 25.33, 26.67, 28.00, 29.33
	3718L _	8-128	9.0, 10.0, 12.0, 14.0, 16.0, 18.0, 20.0, 22.0, 24.0, 26.0, 28.0, 30.0, 32.0, 34.0, 36.0, 38.0, 40.0, 42.0, 44.0

DIMENSIONS & WEIGHTS (NOMINAL)

SIZE	MODELNO.	FITS ²	A LENGTH	B DIAMETER	WEIGHT (LBS)
1/2"	3C0_1	5/8" OD	2.75	0.71	0.1
1/2"L	327_ L	5/8" OD	5.74	0.71	0.5
3/4"	355_ L	7/8" OD	3.96	1.00	0.5
1"	356_ L	1-1/8" OD	9.30	1.76	1.5
1-1/4"	367_ L	1-3/8" OD	9.00	1.76	1.5
1-1/2"	371_ L	1-5/8" OD	6.50	1.76	1.5

NOTES

¹ 1/2", 3/4" and 1-1/2" are basic body sizes. 1/2"L, 1" and 1-1/4" include reducer bushings.

² Fits line size type K, L & M copper tube

Replaces form F-2992 and F-4363


This specification © 2012 Griswold Controls

MODEL NUMBER SELECTION

Select a Housing Size (C0=1/2", 27=1/2"L,
55=3/4", 56=1", 67=1-1/4", 71=1-1/2")

Select a PSID control range:
(1=1-14, 2=2-32³, 4=4-57, 8=8-128)

Select End Code: (1=1/2", L=1/2"L to 1-1/2")



NOTES

³ 1/2" standard requires 2-32 or 4-57 PSID range.

Replaces form F-2992 and F-4363

This specification © 2012 Griswold Controls

2803 Barranca Parkway, Irvine, CA 92606
(949) 559-6000 Fax (949) 559-6088
www.GriswoldControls.com

4/12
F-2992F

