



PRESSURE INDEPENDENT MODULE

SPECIFICATIONS

- PSI/Temperature Rating:** 240 PSI / 250 ° F
Service: Chilled water, hot water, up to 50% Glycol, or contact factory for additional fluids.
Body Material: Cast Iron ASTM A395, 60-40-18
Pipe: Copper
Connections: Grooved End or Flanged¹ (Flanged valve includes grooved to flange adapters that are compatible with ANSI B 16.5-1968 150 lb. Steel flanges)
Cartridge: AISI Type 304 stainless steel
O-rings: EPDM
Accessories: Combination P/T Test Valve and Manual Air Vent (CPTA) Standard

DIMENSIONS & WEIGHTS (NOMINAL) (measured in inches/lbs. unless noted)

SIZE	A HEIGHT	F HEIGHT	G HEIGHT	C DEPTH	E LENGTH	D PIPE LENGTH	WEIGHT
3" FxG	8.8	6.0	2.9	5.8	9.8	2 FT.	18.0
3" FxF					15.8		23.3
3" GxG					15.0		27.0
4" FxG	13.9	8.6	5.3	9.0	21.0		58.0
4" FxF					18.3		65.4
4" GxG					26.8		72.0
6" FxG	17.0	11.3	5.7	11.0	18.3		95.0
6" FxF					26.8		104.9
6" GxG					26.8		125.0

NOTES:

¹ Grooved End by Flanged End shown. Flanged End by Flanged End available and Grooved End by Grooved End available.

FLOW RANGE (+/-5%)

SIZE	MAX PSID	MAX GPM
3"	60	165
4"	60	365
6"	60	505

MODEL NUMBER SELECTION

