

LINE TYPE: <input type="checkbox"/> FNPT <input type="checkbox"/> SWT <input type="checkbox"/> QuickPress ¹		COIL TYPE: <input type="checkbox"/> FNPT <input type="checkbox"/> SWT <input type="checkbox"/> MNPT <input type="checkbox"/> QuickPress ¹	
LINE SIZE: <input type="checkbox"/> 1/2" <input type="checkbox"/> 3/4" <input type="checkbox"/> 1" <input type="checkbox"/> 1-1/4" <input type="checkbox"/> 1-1/2" <input type="checkbox"/> 2"	COIL SIZE: <input type="checkbox"/> 1/2" <input type="checkbox"/> 3/4" <input type="checkbox"/> 1" <input type="checkbox"/> 1-1/4" <input type="checkbox"/> 1-1/2" <input type="checkbox"/> 2"	UNIMIZER SIZE: <input type="checkbox"/> 1/2" <input type="checkbox"/> 3/4" <input type="checkbox"/> 1" <input type="checkbox"/> 1-1/4" <input type="checkbox"/> 1-1/2" <input type="checkbox"/> 2"	
BALL & STEM: <input type="checkbox"/> Nickel-plated brass ball & brass stem <input type="checkbox"/> Stainless Steel ball & stem			
COMPONENT OPTIONS: <input type="checkbox"/> 1-1/2" Ext Kit <input type="checkbox"/> 2" Ext Kit <input type="checkbox"/> Strainer 20 Mesh <input type="checkbox"/> Strainer 50 Mesh <input type="checkbox"/> Isolator S 2 nd CPTA <input type="checkbox"/> Union Coin-Op			
HOSE OPTIONS (FNPT COIL): Swivel Type: <input type="checkbox"/> MNPT <input type="checkbox"/> SWT Length: <input type="checkbox"/> 12" <input type="checkbox"/> 18" <input type="checkbox"/> 24" <input type="checkbox"/> 36"			

SPECIFICATIONS

Unimizer® Actuated Ball Valve: Forged brass (ASTM B283) housing. Valve includes two FNPT fixed ends. Housing assembly includes reinforced Teflon, and EPDM o-ring seals, nickel plated ball, and blow out proof brass stem. Assembly also includes Universal Mounting Plate, shaft, and mounting hardware. PSI/Temperature Rating: 360 PSI / -4°F to 250°F.

Isolator R: Forged brass (ASTM B283) automatic flow control valve assembly includes integrated isolation ball valve and stainless steel flow control cartridge. Cartridge can be removed for inspection, or can be replaced without disturbing piping connections. Valve housing includes field repairable dual Teflon and EPDM o-ring seal stem, with Nickel plated ball. Valve includes one fixed end connection and one union connection. Union end includes union nut and EPDM o-ring. Valve body has two ports with (1) Pressure/Temperature Test Valves, and (1) combination Pressure/Temperature Test Valves and manual air vent (**CPTA**). PSI/Temp Rating: 1/2"–1-1/2": 600WOG-400PSI/250°F. 1-1/2" L–3": 400WOG-275PSI/250°F

Isolator S: Ball valve and integrated strainer. Valve housing is forged brass with field repairable dual Teflon and EPDM o-ring seal stem. Strainer is 20 mesh Stainless Steel and can be removed from housing without disturbing pipe connections for inspection or replacement. Valve includes one fixed connection and one union connection. Union end includes union nut and EPDM o-ring. Body has one port with combination Pressure/Temperature Test Valves (**CPTA**). Assembly includes drain valve with 3/4" hose connection with cap. PSI/Temp Rating: 1/2"–1-1/2": 600WOG-400PSI/250°F. 1-1/2" L–3": 400WOG-275PSI/250°F

Union: Forged brass (ASTM B283) union. Union includes one fixed end (FNPT or SWT) connection and one union (MNPT) connection. Union end includes union nut and EPDM o-ring. Union body has one port with combination Pressure/Temperature Test Valves and manual air vent (**CPTA**). PSI/Temp Rating: 400PSI/250°F

Drain Valve: Brass housing, Nickel plated ball. 1/2"-1": 1/2" UNF x 3/4" NPSH. 1-1/4"-2": 3/4" UNF x 3/4" NPSH. Rated 300PSI/250°F

Combination Pressure/Test Valve & Manual Air Vent (CPTA): Brass Housing, EPDM Seal. Rated 1000PSI/350°F Pressure/Temperature Test Valve works in conjunction with valve body feature to function as Manual Air Vent. Requires both components to operate as manual air vent.

NOTES

¹ QuickPress connections are compatible with popular press tools and are rated for maximum 200 PSI.

MODEL NUMBER SELECTION (R.)

Size	Model Number- FNPT Line	Model Number- SWT Line	Model Number- PRESS Line	Select Coil Size & Type ² for Model Number	Select Unimizer Size for Model Number
1/2"	CP2R0_E_B0U	CP2R0_L_B0U	CP2R0_2_B0U	FNPT:(E=1/2,F=3/4) MNPT:(H=1/2, I=3/4) SWT: (K=3/8",L=1/2,M=3/4) PRESS:(2=1/2,3=3/4)	MNPT:(H=1/2)
3/4"	CP2R0_F_B0U	CP2R0_M_B0U	CP2R0_3_B0U		MNPT:(1/2=H,I=3/4)
1/2"L	CP2R1_E_B0U	CP2R1_L_B0U	CP2R1_2_B0U	FNPT:(E=1/2,F=3/4,G=1) MNPT:(H=1/2,I=3/4,J=1) SWT:(L=1/2,M=3/4,N=1) PRESS:(2=1/2,3=3/4,1=1)	MNPT:(H=1/2)
3/4"L	CP2R1_F_B0U	CP2R1_M_B0U	CP2R1_3_B0U		MNPT:(1/2=H,I=3/4)
1"	CP2R1_G_B0U	CP2R1_N_B0U	CP2R1_1_B0U	FNPT:(G=1,P=1-1/4,Q=1-1/2) MNPT:(J=1,S=1- 1/4,T=1-1/2) SWT:(N=1,K=1-1/4,W=1-1/2) PRESS:(1=1, 4=1-1/4, 5=1-1/2)	MNPT:(1/2=H,I=3/4,J=1)
1"L	CP2R2_G_B0U	CP2R2_N_B0U	CP2R2_1_B0U		MNPT:(1/2=H,I=3/4,J=1)
1-1/4"	CP2R2_P_B0U	CP2R2_K_B0U	CP2R2_4_B0U	FNPT:(P=1-1/4,Q=1-1/2,R=2) MNPT:(S=1-1/4, T=1-1/2,U=2) SWT:(K=1-1/4,W=1-1/2,Y=2) PRESS:(4=1-1/4, 5=1-1/2, 6=2)	MNPT:(1/2=H,I=3/4,J=1,S=1-1/4)
1-1/2"	CP2R2_Q_B0U	CP2R2_W_B0U	CP2R2_5_B0U		MNPT:(1/2=H,I=3/4,J=1,S=1-1/4,T=1-1/2)
1-1/2"L	CP2R3_Q_B0U	CP2R3_W_B0U	CP2R3_5_B0U	FNPT:(P=1-1/4,Q=1-1/2,R=2) MNPT:(S=1-1/4, T=1-1/2,U=2) SWT:(K=1-1/4,W=1-1/2,Y=2) PRESS:(4=1-1/4, 5=1-1/2, 6=2)	MNPT:(S=1-1/4,T=1-1/2)
2"	CP2R3_R_B0U	CP2R3_Y_B0U	CP2R3_6_B0U		MNPT:(S=1-1/4,T=1-1/2,U=2)

Unimizer® Size	Unimizer® Model#	Cv's Available
1/2"	UR2A	.38, .68, 1.3, 2.6, 4.7, 8.0, 11.7
3/4"	UR2B	.31, .63, 1.2, 2.5, 4.3, 10.1, 14.7, 28.6
1"	UR2C	4.4, 9.0, 15.3, 26.1, 28.4, 43.9, 54.2
1-1/4"	UR2D	4.4, 8.3, 14.9, 25.0, 36.5, 41.1, 102.3
1-1/2"	UR2E	22.8, 30.0, 41.3, 73.9, 171.7
2"	UR2F	41.7, 57.0, 71.1, 100.0, 108.0, 210, 266.0

NOTES:

- Standard CPPs include nickel-plated brass ball and brass stem. For optional Stainless Steel ball and stem change "CP" to "CS" in model number.
- Insert PSID Code in 6th digit. Insert "0" for No-Cartridge option.
- Insert Coil Size & Type in 8th digit.
- Insert Unimizer Size in 9th digit.
- Standard CPPs include (1) CPTA in Isolator S with 20 mesh strainer. For optional 2nd CPTA change "B" to "D" (20 mesh) or "G" (1 CPTA – 50 mesh) or "J" (2 CPTA – 50 mesh).
- Optional Extension Kit- includes cap and tube for insulation around handle and appropriate number of extensions for PT/CPTA included in package. Change "0" to "1" for 1-1/2" extension option or "2" for 2" extension option.³

FLOW RATES (+/-5%)

SIZE	IR MODEL NO. FOR REFERENCE	HEAD LOSS IN FEET ⁴	PSID RANGE ⁵	GPM
1/2", 3/4"	IR02	7.4	2-32	0.25, 0.33, 0.50, 0.60, 0.75, 0.85, 1.00, 1.25, 1.50, 2.00, 2.50, 3.00
	IR04	13.4	4-57	0.50, 1.00, 1.50, 2.00, 2.50, 3.00
1/2"L, 3/4", 1"	IR11	3.5	1-14	0.33, 0.50, 0.67, 1.00, 1.33, 1.67, 2.00, 2.33, 2.67, 3.33, 4.00, 4.67, 5.00
	IR12	7.4	2-32	0.55, 0.75, 1.00, 1.25, 1.50, 1.75, 2.00, 2.25, 2.50, 2.75, 3.00, 3.50, 4.0, 5.0, 6.0, 7.0, 8.0
	IR14	13.4	4-57	0.75, 1.00, 1.33, 2.00, 2.67, 3.33, 4.00, 4.67, 5.33, 6.67, 8.00, 9.33, 10.00, 11.00
	IR18	30.0	8-128	1.10, 1.50, 2.00, 3.00, 4.00, 5.00, 6.00, 7.00, 8.00, 10.0, 12.0, 14.0, 16.0
1"L, 1-1/4", 1-1/2"	IR21	3.5	1-14	5.33, 6.00, 6.67, 7.33, 8.00, 8.67, 9.33, 10.00, 10.67, 11.33, 12.00, 12.67, 13.33, 14.00, 14.67
	IR22	7.4	2-32	8.0, 9.0, 10.0, 11.0, 12.0, 13.0, 14.0, 15.0, 16.0, 17.0, 18.0, 19.0, 20.0, 21.0, 22.0
	IR24	13.4	4-57	10.67, 12.0, 13.33, 14.67, 16.0, 17.33, 18.67, 20.0, 21.33, 22.67, 24.0, 25.33, 26.67, 28.0, 29.33
	IR28	30.0	8-128	16.0, 18.0, 20.0, 22.0, 24.0, 26.0, 28.0, 30.0, 32.0, 34.0, 36.0, 38.0, 40.0, 42.0, 44.0
1-1/2"L - 2"	IR31	3.5	1-14	12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38
	IR32	7.4	2-32	18, 21, 24, 27, 30, 33, 36, 39, 42, 45, 48, 51, 54, 57
	IR34	13.4	4-57	24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 68, 72, 76
	IR38	30.0	8-128	36, 42, 48, 54, 60, 66, 72, 78, 84, 90, 96, 102, 108, 114

NOTES

² Coil Type must be FNPT if hoses are required.

³ Extension Option includes handle cover and accessory extensions for either 1-1/2" or 2" Insulation.

⁴ Head Loss in Feet is provided for pump head calculations. (1 PSI = 2.307 Feet of Water)

⁵ Systems with entrained air and fluid velocities less than 4FPS are susceptible to noise when using the 2-32 cartridge. If your system has entrained air and flowrates less than 2GPM please consider using the 4-57 cartridge.